

KRSNA

DYEING

BLEACHING

SCOURING



SPECIFICATION:

CAPACITY: 300 Kgs to 2000 Kgs.

ROLIER FACE: 48" TO 150"

MAIN ROLLER: S.S.316Q – 3mm CLADED

SPEED: 10-100 Mtr./Min.

FABRIC TENSION CONTROL: 0 TO 10 Kgs. [TENSIONLESS OPERATION POSSIBLE]

GSM: SUITABLE FOR ANY TYPE OF FABRIC FROM 30GSM TO 500GSM.

HEATING SYSTEM: BOTH DIRECT AND INDIRECT STEAM [OIL HEATING OPTIONAL]

S.S.QUALITY: SIDE WALL AND SUPPORT 304Q, MAIL ROLL PLUS INNER BOTTOM 316Q

MOTOR: INDIVIDUAL MOTOR FOR TWO MAIN ROLLERS WITH STANDARD MAKE HELICAL BEVEL GEAR BOX.

CONTROL PANEL: ROBUST CONTROL PANEL WITH 2 NOS OF SIEMENS DRIVE WHICH IS SUITABLE FOR AMBIENT

AS PER TROPICAL COUNTRY. SIEMENS PLC & COLOUR TOUCH SCREEN FOR EASY OPERATION.

FEATURES:

AUTO TENSION CONTROL

AUTO SPEED CONTROL

AUTO PENDULUM CONTROL [OPTIONAL]

AUTO CYCLE CONTROL

DOSING SIDE TANK FACILITY [OPTIONAL]

CIRCULATION SYSTEM WITH FILTERS TO AVOID RUNNING CREASE & MACHINE JERKS.

BATCHING OR WINCH DEVICE [OPTIONAL]

AUTO WATER LEVEL CONTROLLER [OPTIONAL]

PNEUMATIC OPERATED DRAIN [OPTIONAL]



FEATURES

AUTO TENSION CONTROL

AUTO SPEED CONTROL

AUTO CIRCULATION SYSTEM

AUTO TEMPERATURE CONTROLLER

AUTO PENDULUM CONTROL [OPTIONAL]

AUTO CYCLE CONTROL

DOSING SIDE TANK FACILITY [OPTIONAL]

CIRCULATION SYSTEM WITH FILTERS TO AVOID CENTER TO SELVEDGE [OPTIONAL]

SUITABLE FOR ANY EXHAUST PRE – TREATMENT, DYEING & FINISH PROCESS.

TENSION SETTING DEVICE TO AVOID RUNNING CREASE & MACHINE JERKS.

FULLY COVERED JIGGER WILL SAVE UTILITIES.

BATCHING OR WINCH DEVICE [OPTIONAL]

AUTO WATER LEVEL CONTROLLER [OPTIONAL]

PNEUMATIC OPERATED DRAIN.

SPECIFICATION:

CAPACITY: 500 Kgs to 2000 Kgs.

ROLIER FACE: 48" TO 150"

MAIN ROLLER: S.S.316Q – 3mm CLADED

SPEED: 10-100 Mtr./Min.

FABRIC TENSION CONTROL: 0 TO 10 Kgs. [TENSIONLESS OPERATION POSSIBLE]

GSM: SUITABLE FOR ANY TYPE OF FABRIC FROM 30GSM TO 500GSM.

HEATING SYSTEM: BOTH DIRECT AND INDIRECT STEAM [OIL HEATING OPTIONAL]

S.S.QUALITY: 304 OUT OUTER BODY 316 MAIL ROLLS PLUS INNER BOTTOM

ROOF HEATING: YES FULLY EFFECTIVE [STEAM HEATING]

CIRCULATION PUMP: CENTRIFUGAL PUMP 3 HP.

DOORS: PNEUMATIC CYLINDERS OPERATED.

MOTOR: INDIVIDUAL MOTOR FOR TWO MAIN ROLLERS WITH STANDARD MAKE HELICAL BEVEL GEAR BOX.

CONTROL PANEL: ROBUST CONTROL PANEL WITH 2 NOS OF SIEMENS DRIVE WHICH IS SUITABLE FOR AMBIENT

AS PER TROPICAL COUNTRY. ETHEMET FACILITY [OPTIONAL]
SIEMENS PLC & COLOUR TOUCH SCREEN FOR EASY OPERATION.



KRSNA ENGINECH PVT.LTD
ADDRESS:B-4, PHASE-II,
NARODA, GIDC
AHMEDABAD 382330 [INDIA]
TEL: +91-79-2282 3093
MOB.No.+91-98250 96234
EMAIL:
[**chandreshshah09@gmail.com**](mailto:chandreshshah09@gmail.com)
[**r.krsnasales@gmail.com**](mailto:r.krsnasales@gmail.com)

WEB: WWW.KRSNAGROUP.IN

